

Product data sheet RWA K 600 T



Retractable arm drive for air intake systems for installation on doors

AREAS OF APPLICATION

- ightarrow Use in the supply air system where large opening angles are required
- → Single and double leaf smoke and heat extraction air-inlet doors
- → Installation on the hinge or opposite hinge side

RWAK 600 T



PRODUCT FEATURES

- → 90° door opening in less than 60 seconds
- → Powerful drive with high torque
- ightarrow Connector cable easy to replace by means of plug
- → Integrated status contact for electric strike control unit or feedback signals
- → Door remains freely accessible due to the freely positioned activation of the lever by means of a pressure roller

TECHNICAL DATA

TECHNICAL DATA			
Productname	RWA K 600 T		
Dimensions	421 x 40 x 56 mm		
Housing material	Aluminum		
Compressive force	600 N		
Operating voltage	24 V DC		
Current consumption	1.4 A		
Residual ripple	20 %		
Duty rating	30 %		
Connector cable length	5 m		
Special length of connector cable	10 m		
Min. core cross section	0.5 mm ²		
Number of cores	5 cores		
Service temperature	-5 - 75 °C		
IP rating	IP32		
protection rating	III		
Synchronising function	Yes		
Adjustable opening speed (ventilation)	Yes		
Additional locking available	Yes		
Type of additional locking mechanism	Locking drive		
End position cut-off extended	Internal path sensor		
End position cut-off retracted	Internal path sensor		
Overload cut-off	Yes		
Number synchronisation drive units	2		
KNX ability	No		

RWAK 600 T



VARIANTS / ORDER INFO

Designation	Description	Ident- No.	Colour	Dimensions	Operating voltage
RWA K 600 T		130059	EV1	421 x 40 x 56 mm	24 V DC
RWA K 600 T 2-leaf with closing sequence - special version	Can be configured: Fixed/active leaf, start-up delay, status contact, colour, free programming	137450	according to RAL	421 x 40 x 56 mm	24 V DC
RWA K 600 T 2-leaf with closing sequence		137449	EV1	421 x 40 x 56 mm	24 V DC
RWA K 600 T - special design	Can be configured: Version master/slave, status contact, colour, opening angle, free programming	130060	according to RAL	421 x 40 x 56 mm	24 V DC

ACCESSORIES

BRACKET G FOR RWA K 600 *

Mounting bracket for K 600 retractable arm drive



BRACKET R FOR RWA K 600 *

Mounting bracket for K 600 retractable arm drive



BRACKET T FOR RWA K 600

Mounting bracket for K 600 retractable arm drive



Designation	Ident-No.	Colour	Dimensions
Bracket T for RWA K 600	140505	according to RAL	100 x 75 x 50 mm

Product data sheet I Page 4 of 4

RWAK 600 T



^{*} The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.