

# Product data sheet Spacer profile 10 mm for concealed wall bracket Perlan 43 mm



Spacer profile for wall installation for leaf thicknesses up to 43 mm

## AREAS OF APPLICATION

- ightarrow For wall installation
- ightarrow For Perlan sliding door fitting
- ightarrow For timber leaves up to 43 mm thickness

### **PRODUCT FEATURES**

ightarrow Spacer profile for tracks for timber leaf installation with a thickness of up to 43 mm

#### TECHNICAL DATA

Productname	Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	
Colour	EV1	

### **VARIANTS / ORDER INFO**

Designation	Description	Ident-No.	Colour
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	for use with "concealed wall bracket up to 43 mm", stackable up to 20 mm spaces	136679	EV1
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	for use with "concealed wall bracket up to 43 mm", stackable up to 20 mm spaces	136711	EV1
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	for use with "concealed wall bracket up to 43 mm", stackable up to 20 mm spaces	136712	EV1
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	bespoke configuration	136717	
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	for use with "concealed wall bracket up to 43 mm", stackable up to 20 mm spaces	136680	EV1
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	for use with "concealed wall bracket up to 43 mm", stackable up to 20 mm spaces	136716	Stainless steel optic
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	for use with "concealed wall bracket up to 43 mm", stackable up to 20 mm spaces	136714	Stainless steel optic
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	for use with "concealed wall bracket up to 43 mm", stackable up to 20 mm spaces	136715	Stainless steel optic
Spacer profile 10 mm for concealed wall bracket Perlan 43 mm	for use with "concealed wall bracket up to 43 mm", stackable up to 20 mm spaces	136713	Stainless steel optic